

SCHUCK TRANSPORT

The complete product range of connection elements for piping systems, used for the transportation of liquid and gaseous media.



SCHUCK TRANSPORT

The complete product range of connection elements for piping systems, used for the transportation of liquid and gaseous media.

Schuck Transport Product Range

	Diameter and Pressure			Temperature								Install
	Nominal diameter inch	Nominal diameter DN	Nominal pressure	Low temperature up to -60°C	Stand. temp range -29°C up to +80°C	Stand. temp. range +1°C up to +50°C	Stand. temp. range +1°C up to +50°C	High temperature up to +120°C	High temperature up to +160°C	High temperature up to +180°C	High temperature up to +200°C	
Valves												
Ball Valve Type G Fully Welded	1/2 - 2	15 - 50	CL150 - 1500	■	■	■	■	■				■
	3 - 12	80 - 300	CL150 - 900	■	■	■	■	■				■
	14 - 60	350 - 1600	CL150 - 900	■	■	■	■	■				■
Ball Valve Type S Split Body	2 - 3	50 - 80	CL150 - 2500	■	■	■	■	■	■			■
	4 - 56	100 - 1500	CL150 - 1500	■	■	■	■	■	■			■
Ball Valve Type U Top Entry	6 - 12	150 - 300	CL150 - 2500	■	■	■	■	■				■
	14 - 24	350 - 600	CL150 - 1500	■	■	■	■	■				■
	28 - 42	700 - 1050	CL150 - 900	■	■	■	■	■				■
Jet Control Check Valve DRV	1 - 24	25 - 600	CL150 - 1500	■		■	■	■				■
	28 - 56	700 - 1500	CL150 - 900	■		■	■	■				■
Insulating Joints												
Insulating Joint SHD	1 - 56	25 - 1500	PN50 - 420	■		■	■	■				■
Insulating Joint SHD for water	3 - 56	80 - 1500	PN50 - 420				■					■
Insulating Joint SHLO for district heating	1 - 56	25 - 1500	PN50 - 420				■	■	■			■
Fittings												
Compensator SDS	3 - 40	80 - 1000	PN50 - 100			■	■					■
Pig Launcher SMO	3 - 60	80 - 1600	up to CL900						1			■
Collector	3 - 60	80 - 1600	up to PN230						1			
T-Fitting	3 - 60	80 - 1600	PN50 - 320						1			■

ation																			
Applications										Connection 1			Connection 2			Sealing System			
Subsurface	Natural gas	Acid gas	Crude oil	District heating	Water	Waste water	Salt water	Drinking water	Other media	Flange	Weld-on end	Waver connection	Flange	Weld-On End	Waver connection	MM (metal to metal)	SO (soft seated)	PMSS (primary metal, secondary soft)	
■	■		■							■	■		■	■		■	■	■	
■	■		■							■	■		■	■		■	■	■	
■	■		■	■	■					■	■		■	■			■	■	
■	■	■	■	■	■	■	■	■	■	■	■		■	■		■	■	■	
■	■	■	■	■	■	■	■	■	■	■	■		■	■			■	■	
■	■	■	■	■	■	■	■	■	■	■	■		■	■			■	■	
■	■		■		■	■		■	■	■	■	■	■	■	■			■	
■	■		■		■	■		■	■	■	■	■	■	■	■			■	
■	■	■							■	■	■		■	■					
■					■	■	■	■	■	■	■		■	■					
■				■					■	■	■		■	■					
■	■									■	■		■	■					
■																			
■																			

■ Standard design | ■ Special design | ¹ According to customers specification



SCHUCK GROUP

Franz Schuck GmbH
Daimlerstraße 4-7
89555 Steinheim, Deutschland

Fon +49. (0) 7329. 950 -0
Fax +49. (0) 7329. 950 -161

info@schuck-group.com
www.schuck-group.com

We manufacture and distribute components for connecting pipeline systems in more than 50 countries, with 5 international offices and over 40 years of experience.

Do you want to find out more about a specific product?
Give us a call, or visit to our website at www.schuck-group.com.



SCHUCK GROUP

DESIGN
ENGINEERING
MANUFACTURING
MADE IN GERMANY